

Nofisol[®]

Black deLUXE

Data sheet

A large red circle containing the text "Black deLUXE" in white.

Black
deLUXE

So much more than just a sound barrier

Nofisol® Black deLUXE

Dimensions Nofisol® Black deLUXE

Length	1200/ 600 mm*
Width	600 mm*
Thickness	15 mm

* Suitable for both T24 and T 15 system

Finish

Front side	Black mineral fleece
Back side	Natural mineral fleece
Sides	Straight A15 of A24

Prestations

Sound absorption – Ceiling

	125 Hz	250 Hz	500 Hz	1 KHz	2 KHz	4 kHz
	0.33	0.64	0.91	0.90	0.88	0.96
Oct 1/3	0.37	0.85	0.93	0.92	0.92	0.96
	0.51	0.90	0.92	0.90	0.95	0.97
Oct 1/1	0.40	0.80	0.92	0.91	0.92	0.96

Absorption
 α_w (ISO 11654)

Class A
0.95

Smoke & Fire behaviour

Euro Fire Class
Stonewool

A1

Specifications

Dimensions



Length	1200/ 600 mm
Width	600 mm
Thickness	15 mm

Finish

Front side	Black mineral fleece
Back side	Naturel mineral fleece
Sides	Straight – A15 or A24

Prestations

Sound absorption	Class A
α_w (ISO 11654)	0.95



Notes

[illegible]

[illegible]



Contact

Everdenberg 9-d
4902 TT Oosterhout

+31 (0) 162 431 231
europa@nofisol.com
www.nofisol.com

Disclaimer

The information in this document is provided for informational purposes only. For project-specific (installation) advice, we recommend contacting us directly.

This product sheet has been compiled based on the current state of the art and applicable laws and regulations. As both legislation and technological developments are subject to change, this product sheet may also be revised accordingly. We strongly recommend always checking whether you have the most recent version of this product sheet. No rights or obligations can be derived from this product sheet.