

# Nofisol<sup>®</sup>

## Black deLUXE

Data sheet



Black  
deLUXE

So much more than just a sound barrier

# Nofisol® Black deLUXE

## Dimensions Nofisol® Black deLUXE

Length	1200/ 600 mm*
Width	600 mm*
Thickness	15 mm

\* Suitable for both T24 and T 15 system

## Finish

Front side	Black mineral fleece
Back side	Natural mineral fleece
Sides	Straight A15 of A24

## Prestations

### Sound absorption - Ceiling

	125 Hz	250 Hz	500 Hz	1 kHz	2 kHz	4 kHz
	0.21	0.63	0.85	0.79	0.90	0.98
Oct 1/3	0.36	0.82	0.91	0.71	0.92	1.00
	0.60	0.84	0.87	0.84	0.96	0.99
Oct 1/1	0.39	0.76	0.88	0.78	0.93	0.99

Absorption  
 $\alpha_w$  (ISO 11654)

Class A  
0.90

### Smoke & Fire behaviour

Euro Fire Class  
Stonewool

A1

# Specifications

## Dimensions

Length	1200/ 600 mm
Width	600 mm
Thickness	15 mm

## Finish

Front side	Black mineral fleece
Back side	Naturel mineral fleece
Sides	Straight - A15 or A24

## Prestations

Sound absorption	Class A
$\alpha_w$ (ISO 11654)	0.90

A15



600x600x15 mm  
1200x600x15 mm

A24



600x600x15 mm  
1200x600x15 mm







## Contact

Everdenberg 9-d  
4902 TT Oosterhout

+31 (0) 162 431 231  
[europa@nofisol.com](mailto:europa@nofisol.com)  
[www.nofisol.com](http://www.nofisol.com)

### Disclaimer

The information in this document is provided for informational purposes only. For project-specific (installation) advice, we recommend contacting us directly.

This product sheet has been compiled based on the current state of the art and applicable laws and regulations. As both legislation and technological developments are subject to change, this product sheet may also be revised accordingly. We strongly recommend always checking whether you have the most recent version of this product sheet. No rights or obligations can be derived from this product sheet.