

Nofisol[®] Seal S

Data sheet



So much more than just a sound barrier

Nofisol® Seal S 60/25



Dimensions Nofisol® Seal S 60/25

Length	1200/ 600 mm*
Height	600 mm*
Thickness	25 mm

*Different dimensions on request

Performance

Sound absorption | Ceiling

125 Hz 250 Hz 500 Hz 1 KHz 2 KHz 4 kHz

	125 Hz	250 Hz	500 Hz	1 KHz	2 KHz	4 kHz
	0.14	0.57	1.01	0.94	0.97	0.94
Oct 1/3	0.31	0.75	0.97	0.87	1.00	0.86
	0.47	0.87	0.95	0.86	0.97	0.77
Oct 1/1	0.31	0.73	0.98	0.89	0.98	0.86

Absorption Class A
 α_w (ISO 11654) 0.95
 SAA (ASTM-C423) 0.89

Sound absorption | Wall

125 Hz 250 Hz 500 Hz 1 KHz 2 KHz 4 kHz

	125 Hz	250 Hz	500 Hz	1 KHz	2 KHz	4 kHz
	0.03	0.12	0.48	0.71	0.92	0.87
Oct 1/3	0.07	0.23	0.56	0.81	0.97	0.85
	0.12	0.35	0.65	0.87	0.94	0.82
Oct 1/1	0.07	0.23	0.56	0.80	0.95	0.85

Absorption Class D
 α_w (ISO 11654) 0.55
 SAA (ASTM-C423) 0.64

Smoke & Fire behaviour

Euro Fire Class

A2-s1,d0

Sustainability



“Building a Greener Future: Certified for Sustainability, Committed to Excellence”

Cradle to Cradle Certified® Bronze v4.0

Globally leading standard that evaluates products across six key areas:

- Environmental Policy and Management;
- Material Health;
- Product Circularity;
- Clean Air and Climate Protection;
- Water and Soil Stewardship;
- Social Fairness.

Eurofins Indoor Air Comfort GOLD


Top indoor quality standards. Our Eurofins Indoor Air Comfort Gold certificate confirms that our products meet strict European VOC emission standards, contributing to a healthier indoor environment.

LCA / EPD

We use Life Cycle Assessments (LCA) and Environmental Product Declarations (EPD) to ensure our products have minimal environmental impact. Listed in both the International and Dutch database.

French VOC A+

Highest standards for low emissions, earning French VOC A+. This rating confirms that our materials emit minimal harmful substances, contributing to superior indoor air quality.



Specifications

Seal S 60/25

Length	600/1200/ on request
Width	600 mm
Thickness	25 mm
Density	60 kg/ m ³

Product details

Foil	Black HDPE foil Micro perforated
------	----------------------------------

Performance

Sound absorption Ceiling	Class A
	α_w (ISO 11654) – 0.95
	SAA (ASTM-C423) – 0.89
Sound absorption Wall	Class D
	α_w (ISO 11654) – 0.55
	SAA (ASTM-C423) – 0.64

Sustainability

Cradle to Cradle Certified®	Bronze v 4.0
Carbon footprint (CO2)	Zero Biogenic Carbon at factory gate
Indoor Air Climate	Class A+
Eurofins VOC	Indoor Air Comfort GOLD version 9.0
LCA – Life Cycle Analyse	PDF Available
EPD – Environmental Product Declaration	PDF Available
PCD – Product Climate Declaration	PDF Available

Database

Eurofins Indoor Air Comfort GOLD	Go to database
Cradle to Cradle – C2C	Go to database
Dutch Environmental Database (NMD)	Go to database
International EPD	Go to database



Contact

Everdenberg 9-d
4902 TT Oosterhout

+31 (0) 162 431 231
europe@nofisol.com
www.nofisol.com

Disclaimer

De informatie in dit document is uitsluitend bedoeld voor informatieve doeleinden. Voor projectspecifiek (installatie)advies raden wij aan om rechtstreeks contact met ons op te nemen.

Dit productblad is samengesteld op basis van de huidige stand van de techniek en de toepasselijke wetten en regelgeving. Aangezien zowel wetten en regelgeving als de stand van de techniek aan veranderingen onderhevig zijn, kan dit productblad eveneens wijzigingen ondergaan. Wij raden sterk aan om altijd na te gaan of u de meest recente versie van dit productblad heeft. Aan dit productblad kunnen geen rechten of verplichtingen worden ontleend.